





服务信



Y7

交流伺服系统
-SERVO

EtherCAT




HCFA
— 禾川科技 —



L



Strong




Y7

20bit

3.5kHz

25bit¹



I B

B

7000
rpm

5000
rpm

350
AX%

300
AX%



OFF	ON



6

3

100Hz

100Hz~5000Hz


XY




Strong 强劲！

Super


“ ”



All-in-one •



•






Safety 安全!





OFF



Y7

Y7



N

- 1 KTY84
- 2 3kW

Technical drawing of a mechanical part, showing a side view and a cross-sectional view (A-A).

Dimensions and Specifications:

- Overall length: 55 (mm)
- Overall width: 65 (mm)
- Material: 20 (Steel)
- Surface finish: 20% 85%RH
- Surface finish: 20% 85%RH
- Surface finish: 5.88m/s²(0.6G)
- Surface finish: 100m/s² (XYZ)
- Surface finish: IP20
- Overall height: 1000m
- Overall width: 1000m

Cross-sectional View (A-A):

The cross-sectional view shows a circular profile with a diameter of 100mm. The profile is divided into two main sections: a top section with a radius of 50mm and a bottom section with a radius of 50mm. The total height of the profile is 100mm. The cross-section is labeled with 'A-A' and '1000m'.

	HN Y A S		EtherCAT		HN Y B S	
	F	E	N	F	E	N
I/O	7DI / 5DO	7DI / 5DO	7DI / 5DO	5DI / 2HDO / 3DO	5DI / 3DO	-
STO	2 AI	2 AI	-	2 AI	-	-
	1 AO	1 AO	-	1 AO	1 AO	-
	✓	✓	✓	✓	-	-
	✓	-	-	✓	-	-
	✓	-	-	✓	✓	-
RS485	✓	✓	-	✓	✓	✓
	✓	✓	-	-	-	-
	✓	✓	-	✓	✓	-





- “✓”

66-77

C



1


14




B1/B2

+
-
















2011

M 200

2023 11

M



Never stop to build up more competitive

6 10%+ 300+

